



IECC 2021 Zūm® Wired Solutions Office Applications

Crestron Electronics, Inc.

Original Instructions

The U.S. English version of this document is the original instructions.

All other languages are a translation of the original instructions.

Crestron product development software is licensed to Crestron dealers and Crestron Service Providers (CSPs) under a limited nonexclusive, nontransferable Software Development Tools License Agreement. Crestron product operating system software is licensed to Crestron dealers, CSPs, and end-users under a separate End-User License Agreement. Both of these Agreements can be found on the Crestron website at www.crestron.com/legal/software_license_agreement.

The product warranty can be found at www.crestron.com/warranty.


The specific patents that cover Crestron products are listed at www.crestron.com/legal/patents.

Certain Crestron products contain open source software. For specific information, visit www.crestron.com/opensource.

Crestron, the Crestron logo, and Züm are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. DALI is either a trademark or registered trademark of IEEE Industry Standards and Technology Organization, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

©2021 Crestron Electronics, Inc.

Zūm® Wired: 0 - 10V Drivers



Bill of Materials

Item	Product	Qty
	ZUMNET-JBOX-16A-LV Zūm Net, Dimmer, 0-10V, 16A	1
	ZUMLINK-JBOX-16A-LV Zūm Link, Dimmer, 0-10V 16A	3
	ZUMLINK-JBOX-20A-PLUG Zūm Link, Plug, 20A	2
	ZUMLINK-KP Zūm Link Keypad, Manual Control	1
	ZUMLINK-DT-QUATTRO-DLS Zūm Link Presence Detector/ Closed-Loop Daylight Sensor	1
	Receptacle	4
	CBL-CAT5E-ZUMLINK-P Zūm Link CAT5e, various lengths	TBD
	CBL-CAT5E-ZUMNET-P Zūm Net CAT5e, various lengths	TBD

Code

Manual Control Device

C405.2.3.1, C405.2.6
Physical control interface for occupant

Occupancy Sensor

C405.2.1, C405.2.1.1
Motion detection: Automatic On, Automatic Off

Vacancy Sensor

C405.2.1.1
Motion detection: Manual On, Automatic Off


Daylight Response

C405.2.4, C405.2.4.1,
C405.2.7.1
Exception C405.2.4.1
Adjust lights based on available daylight

Controlled Receptacles

C405.11, C405.11.1,
Control of receptacle power

Zūm® Wired: 0 - 10V Drivers



Open offices are controlled separately in zones with floor areas no greater than 600 sq ft. When a zone is vacant for 20 minutes, lights automatically reduce by 80%. If all zones are vacant, the lights turn off. For more information, refer to code section C405.2.1.3.

Bill of Materials

Item	Product	Qty
	ZUMNET-JBOX-16A-LV Zūm Net, Dimmer, 0-10V, 16A	1
	ZUMLINK-JBOX-16A-LV Zūm Link, Dimmer, 0-10V 16A	5
	ZUMLINK-JBOX-20A-PLUG Zūm Link, Plug, 20A	1
	ZUMLINK-KP Zūm Link Keypad, Manual Control	1
	ZUMLINK-DT-QUATTRO-DLS Zūm Link Presence Detector/ Closed-Loop Daylight Sensor	4
	GLA-LDL-PC-0-10 Open/Closed Loop Daylight Sensor	1
	CBL-CAT5E-ZUMLINK-P Zūm Link CAT5e, various lengths	TBD
	CBL-CAT5E-ZUMNET-P Zūm Net CAT5e, various lengths	TBD

Code

Manual Control Device

C405.2.3.1, C405.2.6

Physical control interface for occupant

Occupancy Sensor

C405.2.1, C405.2.1.1

Motion detection: Automatic On, Automatic Off

Daylight Response

C405.2.4, C405.2.4.1,
C405.2.7.1


Exception C405.2.4.1
Adjust lights based on available daylight

Controlled Receptacles

C405.11, C405.11.1,

Control of receptacle power

Zūm® Wired: DALI® Drivers



Bill of Materials

Item	Product	Qty
	ZUMLINK-JBOX-20A-PLUG Zūm Link, Plug, 20A	2
	ZUMNET-JBOX-DALI Zūm Net, DALI	1
	ZUMLINK-KP Zūm Link Keypad, Manual Control	1
	ZUMLINK-DT-QUATTRO-DLS Zūm Link Presence Detector/ Closed-Loop Daylight Sensor	1
	Receptacle	4
	CBL-CAT5E-ZUMLINK-P Zūm Link CAT5e, various lengths	TBD
	CBL-CAT5E-ZUMNET-P Zūm Net CAT5e, various lengths	TBD

Code

Manual Control Device

C405.2.3.1, C405.2.6
Physical control interface for occupant

Occupancy Sensor

C405.2.1, C405.2.1.1
Motion detection: Automatic On, Automatic Off

Vacancy Sensor

C405.2.1.1
Motion detection: Manual On, Automatic Off


Daylight Response

C405.2.4, C405.2.4.1,
C405.2.7.1
Exception C405.2.4.1
Adjust lights based on available daylight

Controlled Receptacles

C405.11, C405.11.1,
Control of receptacle power

Zūm® Wired: DALI® Drivers



Open offices are controlled separately in zones with floor areas no greater than 600 sq ft. When a zone is vacant for 20 minutes, lights automatically reduce by 80%. If all zones are vacant, the lights turn off. For more information, refer to code section C405.2.1.3.


Bill of Materials

Item	Product	Qty
	ZUMLINK-JBOX-20A-PLUG Zūm Link, Plug, 20A	4
	ZUMNET-JBOX-DALI Zūm Net, DALI	1
	ZUMLINK-KP Zūm Link Keypad, Manual Control	1
	ZUMLINK-DT-QUATTRO-DLS Zūm Link Presence Detector/ Closed-Loop Daylight Sensor	4
	GLA-LDL-PC-0-10 Open/Closed Loop Daylight Sensor	1
	CBL-CAT5E-ZUMLINK-P Zūm Link CAT5e, various lengths	TBD
	CBL-CAT5E-ZUMNET-P Zūm Net CAT5e, various lengths	TBD

Code

Manual Control Device C405.2.3.1, C405.2.6 Physical control interface for occupant
Occupancy Sensor C405.2.1, C405.2.1.1 Motion detection: Automatic On, Automatic Off
Daylight Response C405.2.4, C405.2.4.1, C405.2.7.1 Exception C405.2.4.1 Adjust lights based on available daylight
Controlled Receptacles C405.11, C405.11.1 Control of receptacle power

Zūm® Wired: 0 - 10V Drivers



Bill of Materials

Item	Product	Qty
	ZUMNET-JBOX-16A-LV Zūm Net, Dimmer, 0-10V, 16A	1
	ZUMLINK-KP Zūm Link Keypad, Manual Control	2
	ZUMLINK-US-HALLWAY-DLS Zūm Link Presence Detector Closed-Loop Daylight Sensor	1
	CBL-CAT5E-ZUMLINK-P Zūm Link CAT5e, various lengths	TBD
	CBL-CAT5E-ZUMNET-P Zūm Net CAT5e, various lengths	TBD

Code

Manual Control Device

C405.2.3.1, C405.2.6
Physical control interface for occupant


Occupancy Sensor

C405.2.1, C405.2.1.1
Motion detection: Automatic On, Automatic Off

Daylight Response

C405.2.4, C405.2.4.1, C405.2.7.1
Exception C405.2.4.1
Adjust lights based on available daylight

Zūm® Wired: 0 - 10V Drivers




Bill of Materials

Item	Product	Qty
	ZUMNET-JBOX-16A-LV Zūm Net, Dimmer, 0-10V, 16A	1
	ZUMLINK-JBOX-16A-LV Zūm Link, Dimmer, 0-10V 16A	3
	ZUMLINK-KP Zūm Link Keypad, Manual Control	2
	ZUMLINK-DT-QUATTRO-DLS Zūm Link Presence Detector/ Closed-Loop Daylight Sensor	2
	GLA-LDL-PC-0-10 Open/Closed Loop Daylight Sensor	1
	CBL-CAT5E-ZUMLINK-P Zūm Link CAT5e, various lengths	TBD
	CBL-CAT5E-ZUMNET-P Zūm Net CAT5e, various lengths	TBD

Code

Manual Control Device C405.2.3.1, C405.2.6 Physical control interface for occupant
Programmable Timeclock C405.2.2.1, C405.2.7.1, C405.2.7.2, C405.2.7.3, C405.2.7.4 Programmed time Auto On, Auto Off
Occupancy Sensor C405.2.1, C405.2.1.1 Motion detection: Automatic On, Automatic Off
Daylight Response C405.2.4, C405.2.4.1, C405.2.7.1 Exception C405.2.4.1 Adjust lights based on available daylight

Zūm® Wired: DALI® Drivers




Bill of Materials

Item	Product	Qty
	ZUMNET-JBOX-DALI Zūm Net, DALI	1
	ZUMLINK-KP Zūm Link Keypad, Manual Control	2
	ZUMLINK-DT-QUATTRO-DLS Zūm Link Presence Detector/ Closed-Loop Daylight Sensor	2
	GLA-LDL-PC-0-10 Open/Closed Loop Daylight Sensor	1
	CBL-CAT5E-ZUMLINK-P Zūm Link CAT5e, various lengths	TBD
	CBL-CAT5E-ZUMNET-P Zūm Net CAT5e, various lengths	TBD

Code

Manual Control Device C405.2.3.1, C405.2.6 Physical control interface for occupant
Programmable Timeclock C405.2.2.1, C405.2.7.1, C405.2.7.2, C405.2.7.3, C405.2.7.4 Programmed time Auto On, Auto Off
Occupancy Sensor C405.2.1, C405.2.1.1 Motion detection: Automatic On, Automatic Off
Daylight Response C405.2.4, C405.2.4.1, C405.2.7.1 Exception C405.2.4.1 Adjust lights based on available daylight

Zūm® Wired: 0 - 10V Drivers



Bill of Materials

Item	Product	Qty
	ZUMNET-JBOX-16A-LV Zūm Net, Dimmer, 0-10V, 16A	1
	ZUMLINK-JBOX-20A-PLUG Zūm Link, Plug, 20A	1
	ZUMLINK-KP Zūm Link Keypad, Manual Control	1
	ZUMLINK-DT-QUATTRO-DLS Zūm Link Presence Detector/ Closed-Loop Daylight Sensor	1
	Receptacle	2
	CBL-CAT5E-ZUMLINK-P Zūm Link CAT5e, various lengths	TBD
	CBL-CAT5E-ZUMNET-P Zūm Net CAT5e, various lengths	TBD

Code

Manual Control Device

C405.2.3.1, C405.2.6
Physical control interface for occupant

Occupancy Sensor

C405.2.1, C405.2.1.1
Motion detection: Automatic On, Automatic Off

Vacancy Sensor

C405.2.1.1
Motion detection: Manual On, Automatic Off


Daylight Response

C405.2.4, C405.2.4.1,
C405.2.7.1
Exception C405.2.4.1
Adjust lights based on available daylight

Controlled Receptacles

C405.11, C405.11.1,
Control of receptacle power

Zūm® Wired: 0 - 10V Drivers



Bill of Materials

Item	Product	Qty
	ZUMNET-JBOX-16A-LV Zūm Net, Dimmer, 0-10V, 16A	1
	ZUMLINK-KP Zūm Link Keypad, Manual Control	1
	ZUMLINK-DT-QUATTRO-DLS Zūm Link Presence Detector/ Closed-Loop Daylight Sensor	1
	CBL-CAT5E-ZUMLINK-P Zūm Link CAT5e, various lengths	TBD
	CBL-CAT5E-ZUMNET-P Zūm Net CAT5e, various lengths	TBD


Code

Manual Control Device
C405.2.3.1, C405.2.6
Physical control interface for occupant

Occupancy Sensor
C405.2.1, C405.2.1.1
Motion detection: Automatic On, Automatic Off

Daylight Response
C405.2.4, C405.2.4.1,
C405.2.7.1
Exception C405.2.4.1
Adjust lights based on available daylight

Zūm® Wired: 0 - 10V Drivers



Bill of Materials

Item	Product	Qty
	ZUMNET-JBOX-16A-LV Zūm Net, Dimmer, 0-10V, 16A	1
	ZUMLINK-JBOX-16A-LV Zūm Link, Dimmer, 0-10V 16A	1
	ZUMLINK-KP Zūm Link Keypad, Manual Control	1
	ZUMLINK-DT-QUATTRO-DLS Zūm Link Presence Detector/ Closed-Loop Daylight Sensor	2
	CBL-CAT5E-ZUMLINK-P Zūm Link CAT5e, various lengths	TBD
	CBL-CAT5E-ZUMNET-P Zūm Net CAT5e, various lengths	TBD


Code

Manual Control Device
C405.2.3.1, C405.2.6
Physical control interface for occupant

Occupancy Sensor
C405.2.1, C405.2.1.1
Motion detection: Automatic On, Automatic Off

Daylight Response
C405.2.4, C405.2.4.1,
C405.2.7.1
Exception C405.2.4.1
Adjust lights based on available daylight

Zūm® Wired: 0 - 10V Drivers



Bill of Materials

Item	Product	Qty
	ZUMNET-JBOX-16A-LV Zūm Net, Dimmer, 0-10V, 16A	1
	ZUMLINK-KP Zūm Link Keypad, Manual Control	1
	ZUMLINK-DT-QUATTRO-DLS Zūm Link Presence Detector/ Closed-Loop Daylight Sensor	1
	CBL-CAT5E-ZUMLINK-P Zūm Link CAT5e, various lengths	TBD
	CBL-CAT5E-ZUMNET-P Zūm Net CAT5e, various lengths	TBD

Code

Manual Control Device

C405.2.3.1, C405.2.6
Physical control interface for occupant

Occupancy Sensor

C405.2.1, C405.2.1.1
Motion detection: Automatic On, Automatic Off

Vacancy Sensor

C405.2.1.1
Motion detection: Manual On, Automatic Off

Daylight Response

C405.2.4, C405.2.4.1,
C405.2.7.1
Exception C405.2.4.1
Adjust lights based on available daylight

Contact Info

Name

Company

Address 1

Address 2

City, State, Zip

Phone

Email

Website

Project Notes

Square Footage	Cost/Sq. Ft.